

Rectifiers

- Nominal output voltage: 48 V
- Nominal output current:

PDB 48/17-800W	- 17 A
PDK 48/20-1000W	- 20 A
PDC 48/41-2000W	- 41 A
PDD 48/67-3200W	- 67 A
PDG 48/120-5800W	- 120 A
- Characteristic: UPI (800, 1000, 2000, 3200, 5800 W)
- Power factor: ~ 1
- Efficiency for rated load: >91%
- Cooling: forced
- Dimensions (HxWxD):

PDB 48/17-800W	- (81x40x285) mm
PDK 48/20-1000W	- (44x88x241) mm
PDC 48/41-2000W	- (88x85,5x273) mm
PDD 48/67-3200W	- (132x85,5x287) mm
PDG 48/120-5800W	- (87x242x375) mm
- Weight:

PDB 48/17-800W	- 1,1 kg
PDK 48/20-1000W	- 1,25 kg
PDC 48/41-2000W	- 2,4 kg
PDD 48/67-3200W	- 3,5 kg
PDG 48/120-5800W	- 8,0 kg
- Digital communications via the control unit
- All connectors on the back panel



PDB 48/17-800W



PDK 48/20-1000W



PDC 48/41-2000W



PDD 48/67-3200W



PDG 48/120-5800W

Certificates:

